

CS-FDG

NOTE:

Please review the product instructions prior to attempting installation to ensure installer is equipped with all tools and capabilities necessary to complete the product installation. We recommend thoroughly reading the instructions at least twice prior to attempting Installation.

Before beginning disassembly of the vehicle, check the “What’s Included” section of the instructions to ensure you’ve received all parts necessary to complete installation. Further, verify that the parts received are PROPER TO YOUR application (year range, motor, etc.) to avoid potential down-time in correcting potential discrepancies. Any discrepancies will be handled by Carli Suspension and the correcting products will be shipped UPS Ground.

LIFETIME PRODUCT WARRANTY

Carli Suspension provides a limited lifetime product warranty against defects in workmanship and materials from date of purchase to the original purchaser for all products produced by Carli Suspension. Parts not manufactured by, but made to Carli Suspension’s specifications by third party manufacturers will carry a warranty through their respective manufacturer. (i.e. King Shocks, Bilstein Shocks, Fox Shocks). Deaver Leaf Spring’s warranty will be processed by Carli Suspension.

Proof of purchase (from the original purchaser only) will be required to process any warranty claims. Carli Suspension products must be purchased for the listed Retail Price reflected by the price listed on the Carli Suspension Website at the time of purchase. Carli Suspension reserves the right to refuse warranty claims made by any customer refusing or unable to present proof of purchase, or presenting proof of purchase reflecting a price lower than Carli Suspension’s Retail Price at the time the item was purchased.

Carli Suspension’s Limited Lifetime Warranty excludes the following parts which are subject to wear: Track Bar Bushings, Track Bar Heim Joints, Limit Straps, Control Arm Bushings, Radius Arm Bushings, Shock Bushings, Sway Bar End Link Heim Joints, Shock Seals, Shock Bearings, and Corrosion on Shock Shafts or Bodies. These items will be warranted for a period of 60 days from the date of purchase only if determined to be installed properly signifying manufacturing defect. Carli Suspension cannot warrant a product’s cosmetic finish due to the varying extreme elements that may be encountered.

Any alterations, modifications, or improper installation, of the product will void this warranty. Products should be inspected for defect upon receipt and approved before installation. Any defect in NEW product will be warranted if returned before installation in its original packaging. Carli Suspension’s obligation under this warranty is limited to the repair or replacement of the defective product only. All costs of removal, installation or reinstallation, freight charges, incidental or consequential damage are expressly excluded from this warranty.

Carli Suspension is not responsible for damages and/or warranty of other vehicle parts related or non-related to the installed Carli Suspension product. This warranty shall not apply to any product that has been subjected to accident, negligence, alteration, abuse or misuse as determined by Carli Suspension. Carli Suspension reserves the right to refuse warranty claims if produced parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension components may cause premature wear and/or product failure. Carli Suspension reserves the right to change/alter product without obligation to update any previously purchased products.



FRONT DIFFERENTIAL GUARD

- 1/4" wall thickness and reinforced design protects your ring & pinion from direct impacts
- Bolts over the factory diff cover, powder coated black



Please Visit: Forums.CarliSuspension.com
Troubleshooting advice or to download an electronic copy of this document.

Fitment

CS-FDG

2003-13: DODGE 2500-3500 4X4 - Diesel

2006-08: DODGE 1500 Megacab 4x4 - Hemi

What's Included in the Kit

- 1 Qty Front Diff Guard
- 7 Qty Bolts

Tools Required for Installation

- Drain Pan
- 3/8 inch Drive Ratchet
- 3/8inch Drive 13mm Socket
- 3/8inch Drive 3 inch Extension

Installation Instructions

- *We recommend installation be done by a trained professional.
- *Read instructions carefully before attempting installation.
- * Re-torque all nuts and bolts Front and Rear after 500 miles to ensure tightness.

- Place drain pan under differential. (You will only lose a couple of drops of fluid during the install)
- Loosen and remove the lower 7 bolts from the Diff Cover.
- Hold Carli Diff Guard flush up to cover and start to thread supplied bolts into differential. Only hand tight @ this time
- Start working your way back and for the tightening up the bolts evenly/equally until you will torque to 25 ft. lbs.